

# KVM Console to USB 2.0 Portable Laptop Crash Cart Adapter with File Transfer and Video Capture, 1920 x 1200 @ 60 Hz

MODEL NUMBER: B032-VU1











Compact unit with built-in cables turns your laptop into a portable console for troubleshooting servers, computers, kiosks and ATMs with no bulky crash cart necessary. Recommended for systems administrators on the move.

# Description

The B032-VU1 KVM Console to USB 2.0 Portable Laptop Crash Cart Adapter with file transfer and video capture turns your laptop into a portable console that connects to servers, computers, kiosks and ATMs. Recommended for busy systems administrators, the B032-VU1 provides direct laptop-to-computer desktop access for file applications, operating system patching, diagnostic testing and software installation. It eliminates the need for unwieldy crash carts.

VGA video and USB keyboard/mouse cables are built into the unit to plug into your server or computer. A USB 2.0 Mini-B cable is included for connecting to your laptop to achieve instant BIOS-level control. You can record videos and capture images from your remote desktop. Bi-directional file transfers between your laptop and connected device occur at USB 2.0 speeds.

The B032-VU1 supports VGA video resolutions up to 1920 x 1200, including 1080p, at 60 Hz. You may adjust picture quality and synchronize mouse pointers for optimum performance. The compact plug-and-play design means no software or external power supply to install, and the unit fits easily inside your laptop bag for immediate use anywhere. It supports hot-plugging, and its firmware is upgradable.

#### **Features**

## **USB Console Adapter Provides Direct Laptop-to-Computer Desktop Access**

- Converts laptop into portable console for servers, computers, kiosks and ATMs
- · Recommended for busy system administrators on the move
- Enables file applications, OS patching, diagnostic testing and software installation
- Eliminates need for bulky crash carts
- Upgradable firmware to keep unit up to date

#### Recommended for Server and PC Troubleshooting

- Instant BIOS-level control
- Bi-directional file transfers between local and remote computer
- · Video recording and image capture of remote desktop

### **Highlights**

- Enables file applications, OS patching and diagnostic testing
- Supports video resolutions up to 1920 x 1200 (1080p) @ 60 Hz
- Instant BIOS-level control
- On-screen keyboard with multilanguage support
- Plug and play—no software or external power supply needed

# **System Requirements**

- · Laptop with available USB port
- Computer with available VGA or DVI-I and USB ports (VGA to DVI adapter needed for DVI-I port)
- Windows® XP or later

### Package Includes

- B032-VU1 KVM Console to USB 2.0 Portable Laptop Crash Cart Adapter
- USB 2.0 A to Mini-B cable, 6 ft.
- Quick start guide



- · Syncs local and remote mouse pointers
- On-screen keyboard with multi-language support
- Supports keyboard pass-through and macros for user-defined hotkeys

#### **Built-In Cabling for Maximum Convenience**

- VGA video and USB keyboard/mouse cables integrated into unit
- $\bullet\,$  Supports VGA video resolutions up to 1920 x 1200, including 1080p, @ 60 Hz
- Adjustable video settings for optimal picture and performance

#### Easy to Use Anywhere

- Compact plug-and-play design—no software or external power supply required
- Fits into laptop bag for immediate use
- Supports hot-plugging

#### **TAA-Compliant**

• Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# **Specifications**

OVERVIEW		
UPC Code	037332201225	
Technology	USB 2.0 (High Speed); VGA/SVGA	
INPUT		
Redundancy - Dual Power Inputs	No	
Bus Powered	No	
PHYSICAL		
Rackmountable	No	
Shipping Dimensions (hwd / in.)	1.70 x 5.00 x 4.90	
Shipping Dimensions (hwd / cm)	4.32 x 12.70 x 12.45	
Shipping Weight (lbs.)	0.50	
Shipping Weight (kg)	0.23	
Unit Dimensions (hwd / in.)	2.130 x 2.880 x 1.880	
COMMUNICATIONS		
IP Remote Access	No	
CONNECTIONS		
Number of Ports	1	



PC/Server Connections	USB; VGA	
FEATURES & SPECIFICATIONS		
NIAP-Certified Secure	No	
Number of Users	1	
On-Screen Display (OSD)	No	
Driver Required	No	
REMOTE ACCESS		
Modem Port	No	
STANDARDS & COMPLIANCE		
Product Compliance	Trade Agreements Act (TAA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.